

SPURT MINIMIZING DISPENSING STRUCTURE

CROSS REFERENCE TO RELATED APPLICATION(S)

Not applicable.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not applicable.

REFERENCE TO A MICROFICHE APPENDIX

Not applicable.

TECHNICAL FIELD

This invention relates to a system for dispensing a product from a container. The invention is especially suitable for a dispensing structure for dispensing high viscosity fluids from a dispensing orifice normally closed by a lid.

BACKGROUND OF THE INVENTION AND TECHNICAL PROBLEMS POSED BY THE PRIOR ART

A variety of packages that include dispensing systems on containers have been developed for household products such as shampoos, lotions, food products and other substances. Such containers typically have a neck defining an open upper end on which is mounted a dispensing closure. The dispensing closure for these kinds of containers typically has a dispensing spout which is covered with a removable lid.

The closure typically has a closure deck or top wall and a depending skirt with an inside bead or thread for attachment to a container. The closure deck includes a dispensing orifice through which a fluid can be dispensed. Depending on the surface tension of the fluid being dispensed through the closure orifice and the coefficient of friction between the fluid and the closure, the fluid tends to cling to the underside of the closure deck and form a layer beneath the dispensing orifice after a dispensing operation. The resulting layer of fluid has a thickness generally dependent on the fluid viscosity.

The lid is typically reclosed to cover the orifice. When the lid is subsequently removed quickly from the closure deck prior to a dispensing operation, the outward movement of the lid has a tendency to immediately cause the fluid in the layer to "spurt", "burp" or otherwise be propelled out of the orifice prior to a controlled, intentional dispensing. The burping of the fluid can cause spatter on the user's hand or clothing or dripping on an exterior surface of the container.

It would be desirable to provide an improved dispensing structure wherein a dispensing orifice in a deck is normally closed by a closure lid which is openable away from a closure deck and wherein the dispensing structure is resistant to propelling fluid upon separation of the lid from the deck.

In addition, it is desirable that the improved dispensing structure design function well with a wide range of fluids, including high viscosity liquids and low viscosity liquids. It would also be beneficial if such an improved dispensing structure design could function well with fluids having different surface tension characteristics.

The present invention provides an improved dispensing structure which can accommodate designs having the above-discussed benefits and features.

SUMMARY OF THE INVENTION

According to one aspect of the present invention, a dispensing structure is provided for a squeezable, fluid holding container so as to eliminate or minimize the propelling or spurting of fluid from a discharge orifice of the dispensing structure during removal or disengagement of a lid which normally closes the discharge orifice. The structure includes a body for closing an opening of the container. The body includes a closure deck having a discharge orifice ordinarily closed by a removable lid. Within the body, and extending from the closure deck, is (1) a conduit, such as a tube, surrounding the orifice and forming a flow channel or passage into the orifice, and (2) a surrounding wall structure, such as an outer ring, around the conduit.

In one embodiment, the surrounding wall structure extends deeper into the container than does the conduit, i.e., the conduit extends to a free end which is recessed upwardly from a free end of the surrounding wall structure.

The surrounding wall structure controls the formation of a "meniscus" of a layer of fluid formed within the discharge structure. The "meniscus" is understood to be a convex or concave surface of a column or layer of liquid. The conduit is sized to extend just beyond the meniscus in order to pierce through the layer of fluid, creating an air path from the interior of the container to the exterior of the container. The conduit acts to break the fluid layer that might otherwise form behind the orifice, thus relieving any pressure behind the layer that would tend to cause the product to "burp" or spurt when the lid is quickly opened. The passage within the conduit is sized such that the surface tension of the fluid resists flow into the conduit. Thus, flow into the conduit will only occur when positive pressure is applied to the contents of the container. Reduced interior pressure (i.e., partial vacuum) created by the container panels returning to their normal position after being squeezed, clears the conduit of fluid.

The diameter and height of the surrounding wall structure and the conduit can vary depending on the fluid and the environment. For example, larger diameters and less height differential are anticipated to be advantageous for more viscous fluids than less viscous, thinner fluids due to the shape and size of the formed meniscus.

The surrounding wall structure can be provided in the form of a ring member extending downwardly from the closure deck or can be formed as a part of the surrounding containment wall of the dispensing structure or container.

In another embodiment, the conduit extends into the dispensing structure as far inwardly as the inner end of the surrounding wall.

In both embodiments, the surrounding wall structure serves to encourage a meniscus to form around the conduit so as to minimize or prevent fluid accumulation in the conduit. The surrounding wall structure allows residual fluid to drip down the surrounding wall structure away from the conduit so as to minimize the tendency of the fluid to enter the conduit.

According to the invention, the dispensing structure can include a lid which may be hinged to, tethered to, or completely removable from, the body of the structure.

The dispensing structure of the present invention may be formed as a unitary part of the container. Alternatively, the dispensing structure may be formed as a separate piece which can be subsequently mounted to the container. Such a dispensing structure in the form of a closure can be designed for attachment to the top of the container by means of a threaded engagement or snap-on engagement.

Numerous other advantages and features of the present invention will become readily apparent from the following detailed description of the invention, from the claims, and from the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawings forming part of the specification, in which like numerals are employed to designate like parts throughout the same,

FIG. 1 is a front perspective view of a first embodiment of the dispensing structure of the present invention shown with the lid open;

FIG. 2 is a cross-sectional view taken generally along plane 2—2 of FIG. 1;

FIG. 3 is a fragmentary, cross-sectional view similar to FIG. 2, but FIG. 3 shows an amount of fluid within the dispensing structure;

FIG. 3A is a fragmentary, cross-sectional view of an alternate embodiment dispensing structure;

FIG. 4 is a fragmentary, cross-sectional view of an alternate embodiment of the dispensing structure, and FIG. 4 shows the dispensing structure mounted on a container.

DESCRIPTION OF THE PREFERRED EMBODIMENT

While this invention is susceptible of embodiment in many different forms, this specification and the accompanying drawings disclose two specific forms as examples of the invention. The invention is not intended to be limited to the embodiments so described, and the scope of the invention will be pointed out in the appended claims.

For ease of description, the dispensing structure of this invention is described in a typical upright position, and terms such as upper, lower, horizontal, etc., are used with reference to this position. It will be understood, however, that the structure may be manufactured and stored in orientations other than the one described.

A first embodiment of a dispensing structure of the present invention is illustrated in FIGS. 1-3 and is designated generally therein by the reference numeral 40. The dispensing structure 40 is provided in the form of a closure 40 which is adapted to be mounted on a container (not illustrated in FIGS. 1-3). The container typically has a conventional mouth or opening formed by a neck or other suitable structure. The neck typically has (but need not have) a circular cross-sectional configuration, and the body of the container may have another cross-sectional configuration, such as an oval cross-sectional shape, for example.

The container may be a squeezable container having a flexible wall or walls which can be grasped by the user and compressed to increase the internal pressure within the container so as to squeeze the product out of the container through the closure when opened. The container wall typically has sufficient, inherent resiliency so that when the squeezing forces are removed, the container wall returns to its normal, unstressed shape. Such a structure may be preferred in some applications, but may not be necessary or preferred in other applications. For example, the container may be rigid or substantially rigid and other means used to cause a dispensing force on the fluid within the container.

With reference to FIG. 1, the closure 40 includes a base or body 46 and preferably includes a lid 48 connected to the base or body 46 with a hinge 47. The lid 48 is adapted to be moved between (1) a closed position (not illustrated) in which the lid 48 is sealingly engaged with the closure body

46 to prevent unintentional dispensing of a fluid from the container to which the closure is mounted, and (2) the illustrated open position in which the lid 48 is disengaged from the top of the closure body to permit dispensing of the liquid through the closure.

Preferably, the hinge 47 is a snap-action hinge formed integrally with the lid 48 and body 46 in a unitary structure. The illustrated snap-action hinge 47 may be a conventional type described in U.S. Pat. No. 4,403,712. Other hinge structures may be employed, including a "floppy" living film hinge. However, it is preferable to employ a snap-action hinge so as to be able to readily maintain the hinge 47 and lid 48 in the open position during the dispensing of the liquid from the container.

The base or body 46 is preferably injectionmolded, along with the hinge 47 and lid 48, from a thermoplastic material compatible with the container contents.

The body 46 includes an annular mounting skirt or lower wall 56. The skirt or wall 56 defines an opening 57 (FIG. 2) which is adapted to receive the container neck and which is adapted to completely encompass the container neck opening.

The wall 56 may have suitable attachment means (e.g., a conventional thread 55 (FIG. 2) or conventional snap-fit bead (not illustrated)) for engaging a suitable container cooperating means, such as a complementary thread or bead on the container neck, to secure the closure body 46 to the container. The closure body 46 and container could also be fixed together by induction melting, ultrasonic melting, gluing, or the like. The closure could also be formed as a unitary part of the container neck.

Formed at the top of the annular mounting skirt 56 is a top wall portion or deck 58. The deck 58 extends radially inwardly over the opening 57 defined by the annular mounting skirt 56. The deck 58 defines a smaller, dispensing orifice 60 located above the opening 57 defined by the mounting skirt 56.

The container and closure 40 may be normally stored in the upright orientation wherein the closure 40 is at the top of the container. The orifice 60 would be above the opening defined by the container neck when the closure 40 is mounted on the container. The closure lid 48 would typically be closed over the body deck 58 when liquid is not being dispensed from the container.

The deck 58 includes a raised platform 70. The lid 48 includes an annular ring 72 having a beveled surface 72a which is adapted to be guided by an edge 70a of the platform 70 when the lid 48 is closed over the body 46. The beveled surface 72a acts to center the lid 48 onto the platform 70 of the body 46.

The deck 58 also includes a spout 80. The spout 80 extends in a smooth, curved transition from the platform 70. The platform 70 extends outwardly of, and extends continuously around, the spout 80. The orifice 60 extends through an outer end of the spout 80. In order to use the closure 40, the lid 48 is opened to the position illustrated in FIG. 1. Then the container, with the closure 40 mounted thereon, is tilted forwardly and downwardly. Fluid can then be squeezed out of the container through the spout 80 and dispensing orifice 60.

Within the lid 48, and particularly concentrically located within the annular ring 72, is a collar 84 having a beveled lip 85 and an annular seal bead 86. The collar 84 is located such that when the lid 48 is closed to engage the body 46, the bead 86 sealingly engages the exterior surface of the spout 80.

The lid 48 includes an outer annular wall 90 having a rim 91 which abuts top shoulders 92a, 92b (shown in FIG. 1) of

6

5

10

15

20

25

39

50

5

10

20

25

39

40

40

45

55

6